


**DELPHION**
[Log Out](#) [Work Files](#) [Saved Searches](#)
[My Account](#)
[Search:](#) Quick Number Boolean Advanced Derwent
[RESEARCH](#)[INVENTORIES](#)[LINKED DOCUMENTS](#)**The Delphion Integrated View**Get Now:  PDF | [File History](#) | [Other choices](#)Tools: Add to Work File:  Create new \View: [INPADOC](#) | Jump to: [Top](#) [Go to: Derwent](#) [Email](#)

**Title:** [JP01287132A2: NONFLAMMABLE RESIN COMPOSITION](#)

**Derwent Title:** Flame-retardant resin compsn. - contg rubber-like material and copolymer contg unsatd nitrile including mono-vinyl aromatic cpd [\(Derwent Record\)](#)

**Country:** [JP Japan](#)

**Kind:** A (See also: [JP07035464B4](#) )



**Inventor:** TOHARA AKIHITO;  
SUGIMOTO TSUTOMU;  
TAKAHASHI YASUSHI;  
ISHIKAWA CHUKEI;

**Assignee:** ASAHI CHEM IND CO LTD  
[News, Profiles, Stocks and More about this company](#)

**Published / Filed:** 1989-11-17 / 1988-05-16

**Application Number:** [JP1988000116836](#)

**IPC Code:** Advanced: [C08G 59/30](#); [C08G 59/40](#), [C08L 53/02](#); [C08G 59/06](#);  
Core: [C08G 59/00](#); [C08L 53/00](#);  
IPC-7: [C08G 59/30](#);  
[C08G 59/40](#);

**Priority Number:** 1988-05-16 [JP1988000116836](#)

**Abstract:** PURPOSE: To obtain a styrene-based resin composition useful for housing material of business machine or electric apparatus having excellent impact resistance, light-resistance and fire resistance containing respectively specific resin composition and halogen-containing compound in a specific ratio

CONSTITUTION: (A) 100pts wt. resin composition, obtained by polymerization of monovinyl aromatic monomer and unsaturated nitrile monomer in the presence of rubber-like material and containing 8W24wt % rubber-like material, 76W92wt % copolymer of monovinyl aromatic compound unit and unsaturated nitrile compound unit and a fraction of unsaturated nitrile compound unit in said copolymer is 20W27wt % is mixed with (B) 12W26pts wt halogen-containing compound expressed by the formula (X is Br or C; a, b, c, d is 1W4; n is natural number), having 80W110°C softening point and epoxy groups on both chain ends to afford the aimed composition


COPYRIGHT: (C)1989,JPO&Japio

**INPADOC Legal Status:** None [Get Now: Family Legal Status Report](#)


**Family:** [Show 2 known family members](#)

**Other Abstract Info:** [DERABS C90-004089 DERC90-004089](#)

**BEST AVAILABLE COPY**



[Nominate this for the Gallery...](#)



THOMSON

Copyright © 1997-2006 The

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Cont](#)

BEST AVAILABLE COPY